

# Penetrating Oil SL-10™

Heavy-duty penetrating oil and spray lubricant designed to quickly penetrate into hard-to-reach areas to loosen seized and corroded nuts and bolts and provide long-lasting lubrication

### **Key Features & Benefits**

- Dual function: Fast-acting penetrating oil and heavy-duty lubricating action
- Penetrates into hard-to-reach areas
- Loosens seized and corroded nuts and bolts or other frozen metal mechanisms
- · Protects against rust and corrosion
- The better alternative to an aerosol can... the spray bottle is safer and full of product... no money wasted on hazardous ozone-depleting substances
- Contains Muscle Metal Treatment MT-10<sup>®</sup> technology Power-Lift Grease PL-10<sup>™</sup> for enhanced lubrication

## **Typical Applications**

- · Rusty nuts & bolts
- · Heavy-duty industrial chains
- · Braided steel cables
- Wire rope
- Chain drives
- Drag lines
- Linkages
- Open roller bearings and sleeve bearings
- Couplings
- Bushings
- Pulleys
- Hinges
- Augers
- Tools
- Metal mechanisms
- Assembly lube during transmission rebuilds

- Protection during long-term storage
- Any other industrial, automotive, or commercial area of lubrication that requires an external, heavy-duty penetrating oil or spray lubricant.

# **Directions for Use**

Wipe off exposed metal surfaces. Spray **SL-10**<sup>™</sup> directly onto areas to be lubricated. After application, wipe away excess **SL-10**<sup>™</sup> with a dry cloth. Repeat in especially stubborn applications.

### **Technical Data**

Appearance	Milky amber liquid
Odor	
Boiling point	399°F (204°C) D1120
Flash point	295°F (146°C) D93
Specific gravity @ 60°F, g/cm <sup>3</sup> .	0.933 D1298
Lbs per gal (U.S.)	~ 7.785
Viscosity @ 40°C	
Pour point	33°F (-36°C) D97
Rust test, 4 hr	Pass (no rust) D665A
Solubility	Insoluble (water)

The above properties are typical values and do not constitute a product specification.

## **Container Availability**

Item SL-10-16WS	16 oz. w/sprayer (473 mL)
Item SL-10-128	1 U.S. gallon (3.7 L)
Item SL-10-5G	5 U.S. gallon (18.9 L)
Item SL-10-55G	55 U.S. gallon (208 L)

© 1986-2015 Muscle Products Corp. R.07

