



Power-Lift Grease PL-10™

Absolutely one of the best anti-wear, extreme-pressure, lithium complex greases designed to meet the highest requirements for film strength, operating temperatures and lubrication life – essential for the reliable operation of today's equipment

Key Features & Benefits

- Provides extreme-pressure protection under all lubrication conditions
 - Lowers operating temperatures
 - Protects from friction-related heat and wear
 - Protects against rust and corrosion
 - Extends equipment life
 - Reduces maintenance, downtime and related expenses
 - Excellent water washout and spray off resistance
 - Continuous operating range: 0°F to 450°F (-17°C to 232°C)
 - Typical dropping point: 525°F+ (273°C+)
 - NLGI #2 (other grades may be available on request)
 - Contains **Muscle Metal Treatment**
MT-10® technology for increased lubricity and boundary film lubrication
 - Treats, seals and protects metal surfaces for reduced friction and wear

Typical Applications

- Bearings
 - Disc brake wheel bearings
 - Universal joints
 - CV joints
 - Chassis fittings
 - Axles
 - Conveyors
 - Pumps
 - Firearms
 - Fishing reels and tackle
 - Sports equipment
 - Other industrial, automotive or commercial areas of lubrication requiring an extreme-pressure, anti-wear grease

Technical Data

Appearance	Cream, smooth/tacky semi-solid
Odor	Bland
NLGI grade	2
Thickener type	Lithium
Soap type	Lithium complex
Antirust corrosion inhibitor.....	Yes
Corrosion test	Pass
Base oil viscosity @ 40°C, SUS.....	775 - 825
Cone penetration @ 77°F, 60 strokes.....	265-295
100,000 strokes	+10%
Dropping point	> 525°F (> 273°C)
Pour point	0°F (- 17.8°C)
Density @ 20°C, g/cm ³	1.0216
Lbs per gal (U.S.)	~ 8.525
Flash point	> 437°F (> 225°C)
Fire point.....	580°F (304°C)
Roll stability.....	+/- 6
Oxidation PSI @ 100 hr., 500 hr	5, 10
Timken OK Load, lbs	60
Shear stability	< 10%
Wheel bearing, % loss	0 - 1
Four-ball weld point, kg	1000
Four-ball wear, mm	0.56
Water resistant.....	Yes
Water washout @ 170°F.....	3 - 8
Mobility, g/min 0°C, 20°C	3, 35
Solubility	Negligible (water)

The above properties are typical values and do not constitute a product specification.

Container Availability

Item PL-10-T.....	1 oz. tub (28 g)
Item PL-10-C	14 oz. cartridge (396 g)
Item PL-10-LB.....	16 oz. tub (453 g)
Item PL-10-5LB.....	72 oz. tub (2 kg)
Item PL-10-P.....	35 lb. pail (15.8 kg)
Item PL-10-K.....	120 lb. drum (54 kg)
Item PL-10-D.....	400 lb. drum (181 kg)

Transportable tank and other bulk container availability upon request

© 1986-2015 Muscle Products Corp. B 05



AUTHORIZED DISTRIBUTOR

2230 S PROSPECT AVE, OKLAHOMA CITY, OK 73129
(405) 677-4444 | hh-preorder@horizonhydraulics.com